

IsoPurge 1000

IsoPurge 1000 is a safe, non-hazardous hot melt -cleaning compound. IsoPurge 1000 helps reduce downtime and increases productivity. IsoPurge 1000 was designed for purging polyurethane reactive hot melt adhesives from hot melt application equipment to prevent the cured hot melt from clogging machines and tips.

*Values given are not intended to be used in specific preparation

Component Properties

Color	Green
Viscosity - ASTM-D-2196 - 350°F, ISO	6000 - 8000 cps

PRODUCT ADVANTAGES

- 100% Solids
- Can be dispensed via a Cartridge
- No mixing required
- One Component

RECOMMENDED HANDLING INSTRUCTIONS

Application temperature of IsoPurge 1000 is between 250-350°F. Use at the same application temperature as the glue.

Use IsoPurge 1000 at the processing temperature of the system.

Purge the system until the extruded material is dark green.

STORAGE

Store in a cool, dry place.

SAFETY

-Refer to the product SDS for all relevant safety information.

Date Modified 1/31/2022

Since Seller exercises no control over Buyers application or use of the product manufactured by Seller ("product") and since materials used with the product may vary, it is understood that:

- THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OR MECHANABILITY OR FOR ANY PARTICULAR PURPOSE. While all data presented in Seller's technical data sheet is based on the best information available to Seller and believed correct, such data is not to be construed as a warranty that the product will conform to such specifications. Such technical data sheets are subject to change without notice. Reported laboratory test results of fire redundancy in no way relates to the actual performance under fire conditions. Since all urethane systems are organic, they will burn.
- Reported laboratory test results of the color stability in no way relates to the actual performance upon exposure to light sources. Since all aromatic urethanes experience color degradation upon ultraviolet light exposure, Seller shall not be liable for any damages resulting from ultraviolet light color degradation of any aromatic urethane systems manufactured or sold by Seller.
- The liability of the Seller shall not exceed the purchase price and the Buyer shall not be entitled to nor the Seller be liable for any consequential, incidental, indirect or special damages resulting in any manner from the furnishing of the product.

www.isotecintl.com

"The Chemistry Behind Performance"[®]

(800) 234-6300